

GZ071A
INTERPON D1000 GENERIC MSDS
Version No. 10 Date Last Revised 09/05/2013

Safety Data Sheet

Customer Not Specified

Sales Ord. No :

Product Code GZ071A Date Sent 5/09/2013

1. Product and company identification

Not Hazardous according to criteria of Australian WHS Regulations.

Not classified as a Dangerous Good for transport according to the latest ADG code.

Product Name	INTERPON D1000 GENERIC MSDS
Product Code	GZ071A
Intended use	This product is intended for use in the powder coatings market. Refer Technical Data Sheet. For professional use only.
Application Method	Refer Technical Data Sheet.
Company Name	Akzo Nobel Pty Limited 51 McIntyre Road Sunshine North Victoria 3020 Australia

Telephone No.	(03) 9313 4555
Fax No.	(03) 9311 9141
24 hour Emergency Telephone No.	1800 680 071
For Poisons Advice telephone	131 126 For Advice to Doctors & Hospitals only

2. Hazard Identification

S23 - Do not breathe vapour/spray.

S51 - Use only in well-ventilated areas.

Poison Schedule: None Assigned or Not Applicable.

Precautionary Phrases (P) listed below:

3. Composition / information on ingredients

This product contains the following substances that are classified hazardous according to the Australian WHS Hazardous Substances regulations:

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



GZ071A
INTERPON D1000 GENERIC MSDS
Version No. 10 Date Last Revised 09/05/2013

Ingredient	CAS Number	Concentration Range%	Risk phrases (*)
N,N,N',N',-tetrakis (2-Hydroxyethyl) Hexanediamide	0006334-25-4	1-2.5	
Aluminium hydroxide	0021645-51-2	1-2.5	Xi Irritant R36 R37

Other ingredients in this product have been determined not to be hazardous

* The full text of the above phrases are shown in section 16.

* Cut of levels for labelling Risk and Safety Phrases are shown in section 15.

4. First aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation

Not expected to be acutely toxic by inhalation.

All dusts are irritants, therefore inhalation of dusts should be avoided. Exposures to high dust concentrations may cause irritation to the mucous membrane of the respiratory system and the eyes.

Symptoms may include reddening, swelling, itching, weeping, sneezing and coughing.

Wash out nose and mouth with water. Remove to fresh air if any effects apparent. Seek medical attention if any effects persist.

Eye Contact

Expected to cause no more than minor eye irritation. Dust in the eyes may cause irritation or corneal injury due to mechanical action.

Irrigate copiously with clean fresh water for 10 minutes, holding eyelids apart. Seek medical attention if irritation persists.

Skin Contact

Skin contact may cause mild irritation. Prolonged and/or repeated contact may lead to irritant contact dermatitis.

Wash effected areas with soap and water. Seek medical attention if irritation persists.

Ingestion

Moderately toxic when ingested.

Thoroughly rinse mouth with clean water.

If swallowed DO NOT induce vomiting. Give a glass of water to achieve effective dilution. Seek medical attention.

5. Fire-fighting measures

This product is combustible.

Material will burn, emitting carbon oxide combustion products.

Possibility of dust explosions, depending on the dust concentration in the air and ignition sources present.

Recommended extinguishing media; water spray, foam (large fires) - CO₂, powder (small fires). When

entering enclosed areas, wear self contained breathing apparatus.

Do not allow contaminants and water from fire fighting to enter drains or water courses.

6. Accidental release measures

Wear protective equipment as listed in Section 8 during clean up operations.

Vacuum spills to keep dust down, do not sweep. Ventilate area.

Do not allow into water courses.

If drains, sewers, streams or lakes are contaminated contact the relevant Environment Protection Agency or local authority.

7. Handling and storage

Handling

Handle carefully as the powder is very fine and can spread. Handlers of powders should wash hands and face prior to meals and smoking.

In Storage

Handle containers carefully to prevent damage and spillage.

In Use

Avoid skin and eye contact. Avoid inhalation of dust. Observe label precautions. Use personal protection equipment as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Storage

Store in a cool dry area (below 25C), away from heat, sparks and open flame.

Keep containers sealed when not in use.

Store out of direct sunlight.

8. Exposure controls and personal protection

Engineering Measures

Good housekeeping is required to keep airborne dusts to a minimum to avoid the possibility of dust explosions. Take care to clean down all horizontal surfaces where dust can accumulate.

Ensure all equipment is correctly earthed.

Use local exhaust ventilation and / or general ventilation to maintain dust levels below the recommended exposure limits. Exhaust ventilation is required at the point of application. This should be sufficient to maintain levels below the recommended exposure standards.

Application of this product should be in accordance with AS/NZS3754 (Safe Application of Powder Coatings by Electrostatic Spraying).

Exposure Limits

From Australia's Hazardous Substance Information System (HSIS)

For detailed information refer to the HSIS web site (<http://hsis.ascc.gov.au>).

GZ071A
INTERPON D1000 GENERIC MSDS
Version No. 10 Date Last Revised 09/05/2013

Material	Short term (15m ave STEL)		Long term (8hr TWA)	
	ppm	mg/M3	ppm	mg/M3

Chemicals classified as hazardous according to WHS regulations may have a notification alongside the exposure standard. If such a notification is necessary, it will appear in the far right hand column. The legend is as follows:

- (P) Peak exposure limit
- (R) Suppliers Recommended Limit
- (Sk) There is a risk of absorption through unbroken skin
- (Sen) Sensitiser
- (Cat1) Category 1 - established human carcinogen
- (Cat2) Category 2 - probable human carcinogen
- (Cat3) Category 3 - substances suspected of having carcinogenic potential.

There is no biological limit allocated.

Personal Protection

For Professional Applications (Indoor and Outdoor) the maximum daily exposure allowed is less than or equal to 8 hours. This is for natural, local exhaust or no ventilation wearing the PPE requirements highlighted above.

Respiratory Protection

In ventilated areas and spray booths that will maintain exposure levels below the recommended limits - no respiratory equipment is required.

If exposed to dust, wear a dust mask or cartridge respirator fitted with a dust cartridge. In confined areas, use an approved air line respirator or hood.

Refer to AS/NZS1715 Selection, use and maintenance of respiratory protection devices.

Eye Protection

Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

Hand Protection

Wear PVC or rubber gloves.

Skin Protection

Wear overalls to keep skin contact to a minimum. Users of this product may also consider using hoods or balaclava's to protect the face.

9. Physical and chemical properties

Physical State	Powder
Colour	Coloured
Flash Point (deg C closed cup)	N/A
Autoignition temperature	9
Viscosity (cSt)	N/A
Specific Gravity	1.465
Solvent Weight %	Not Applicable

Vapour Density	Heavier than air.
pH	Not Applicable
Lower Explosive Limit	>N.o ()
Upper Explosive Limit	No data available ()
Solubility in Water	Immiscible
R.A.Q. to ventilate to 10% of the LEL (M3/l)	-
Odour	No smell

10. Stability and reactivity

This product is stable under normal storage and handling conditions (see section 7). When exposed to very high temperatures, may produce hazardous decomposition products such as carbon monoxide, oxides of nitrogen and smoke.

11. Toxicological information

There are no data available on the product itself.

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.



GZ071A
INTERPON D1000 GENERIC MSDS
Version No. 10 Date Last Revised 09/05/2013

12. Ecological information

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

13. Disposal considerations

Vacuum spills to keep dust down, do not sweep.

Do not allow into drains or watercourses.

As waste regulations vary, use information provided in this data sheet to obtain advice from the local Waste Regulation Authority.

14. Transport information

Transport only in accordance with the following regulations:

Road and Rail Transport (ADG7) Non Hazardous

{otherlabel} {OtherTrans}

IMDG reference :	Class/Div.	Subsidiary Class
	Proper Shipping Name	Non Hazardous
	UN No.	MFAG
	EMS	
	Packaging Group	
	Marine pollutant	No

ICAO/IATA	Shipping Name
	Class
	UN No.
	Packaging Group

15. Regulatory information

The following information is provided in accordance with Safework Australia guidelines for the labelling of Hazardous Substances.

Symbol(s)

Contains;

Risk (R)Phrases;

Safety (S)Phrases;

S23 - Do not breathe vapour/spray.

S51 - Use only in well-ventilated areas.

Precautionary (P)Phrases;

16. Other information

Contact point:

Industrial Coatings HSE Department - Health and Safety Advisor
+61 (0)3 9313 4555

Marine & Protective Coatings Regulatory Affairs Manager
+61 (0)3 8336 8487

The information on this MSDS is based upon the present state of our knowledge and on current State and Federal laws.

The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Material Safety Data Sheet is required according to State and Federal legislation and following Safework Australia's guidance (as amended).

The full text of the Hazard (H) phrases appearing in section 2 & 3 are:

R36: R36 - Irritating to eyes.

R37: R37 - Irritating to respiratory system.

Xi: Irritant

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.

